

## AMENDMENTS TO THE CLAIMS

1. (Currently amended) A method of selecting at least one routing path between an access node and at least one of a plurality of gateways comprising:  
each gateway originating and broadcasting beacons over a plurality of channels, the beacons being broadcast over each of the plurality of channels at a predetermined rate;  
the access node receiving over a plurality of channels, ~~indicators~~ beacons from at least one upstream access node ~~or gateway~~, the ~~indicators~~ beacons providing information of selected upstream paths to at least one of between each of the upstream access nodes and upstream the plurality of gateways; and  
the access node selecting a determining an optimal set of routing paths between the access node and at least one upstream of the plurality of gateways, based on a persistence of successfully received beacons upon the indicators, the optimal set of selected routing paths including a combination of paths over multiple channels;  
the access node re-broadcasting beacons corresponding to the selected routing path, over each of the plurality of channels.
2. (Previously Presented) The method of claim 1, wherein the plurality of channels comprises transmission channels according to at least two of 802.11(a), 802.11(b), 802.11(g), 802.11(n) transmission protocols.
3. (Cancel) The method of claim 1, wherein the access node determining an optimal set of routing paths comprises determining a path quality of the available paths, and selecting the optimal paths based upon a selection criteria.

4. (Currently Amended) The method of claim [3] 1, wherein the selection criteria is additionally based upon an information throughput of the routing paths.
5. (Currently Amended) The method of claim [3] 1, wherein the selection criteria is additionally based upon a number of hops of the routing paths.
6. (Cancel) The method of claim 1, wherein the optimal set of routing paths includes at least one of a plurality of possible routing paths.
7. (Cancel) The method of claim 1, wherein the optimal set of routing paths includes a combination of paths through multiple upstream access nodes.
8. (Cancel) The method of claim 1, wherein the indicators comprise beacons originating at the gateways, wherein the gateways broadcast the beacons over multiple channels.
9. (Currently amended) The method of claim [8] 1, wherein beacons that are successfully received by the upstream access nodes are retransmitted rebroadcast by the upstream access nodes over multiple channels after the beacons have been modified to include selected upstream routing information of the upstream access nodes.
10. (Cancel) The method of claim 8, wherein the beacons comprise hop indicators that are incremented with each hop.
11. (Currently amended) The method of claim [9] 1, wherein selected upstream paths between each upstream access node and upstream gateways includes a combination of paths, over multiple channels, and upstream paths are selected

based on a persistence of successfully received broadcast and rebroadcast beacons.

12. (Original) The method of claim 1, wherein selected upstream paths between each upstream access node and upstream gateways are selected based upon path quality.
13. (Original) The method of claim 12, wherein the path quality is determined by an information throughput of the upstream paths.
14. (Original) The method of claim 12, wherein the path quality is determined by a number of hops included within the upstream paths.
15. (Currently amended) The method of claim 1, further comprising the access node transmitting a modified ~~indicator~~ beacon over a plurality of channels, the modified indicator including the optimal set of routing paths between the access node and the at least one upstream gateway.
16. (Original) The method of claim 1, further comprising:
  - sending a reverse beacon to the gateway; and
  - constructing a client tree in the gateway, wherein the gateway has at least one path including multiple channels to all clients.
17. (Currently amended) A method of routing data packets through a wireless mesh network, the mesh network comprising at least one gateway and a plurality of access nodes, the method comprising:

each gateway originating and broadcasting beacons over a plurality of channels, the beacons being broadcast over each of the plurality of channels at a predetermined rate;

each access node receiving over a plurality of channels, beacons ~~indicators~~ from at least one upstream device;

if the at least one upstream device is an upstream access node, the indicators providing information of selected upstream paths between each of the upstream access nodes and upstream gateways; and

each access node determining an optimal set of routing paths between the access node and at least one upstream gateway, based upon a persistence of successfully received ~~the~~ indicators, the optimal set of routing paths including a combination of paths over multiple channels.

18. (Original) The method of claim 17, wherein the plurality of channels comprises transmission channels according to at least one of 802.11(a), 802.11(b), 802.11(g), 802.11(n) transmission protocols.
19. (Cancel) The method of claim 17, wherein the access node determining an optimal set of routing paths comprises determining a path quality of the available paths, and selecting the optimal paths based upon a selection criteria.
20. (Cancel) The method of claim 17, wherein the indicators comprise beacons originating at the gateways.
21. (Currently amended) The method of claim ~~20~~ 17, wherein the beacons are retransmitted by the upstream access nodes after the beacons have been modified to include selected upstream routing information.

22. (Original) The method of claim 17, wherein selected upstream paths between each upstream access node and upstream gateways can include a combination of paths, over multiple channels.
23. (Currently amended) The method of claim 17, further comprising the access node transmitting a modified ~~indicator~~ beacons over a plurality of channels, the modified ~~indicator~~ beacons including the selected optimal set of routing paths between the access node and the at least one upstream gateway.
24. (Original) The method of claim 17, further comprising  
sending a reverse beacon to the gateway; and  
constructing a client tree in the gateway, wherein the gateway has at least one path including multiple channels to all clients.
25. (Currently amended) An access node comprising:  
a plurality of radios operable on a plurality of transmission channels, the radios simultaneously receiving over each of a plurality of channels, indicators from at least one upstream access node, the indicators providing information of selected upstream paths between each of the upstream access nodes and upstream gateways; and  
means for determining an optimal set of routing paths between the access node and at least one upstream gateway, based upon a persistence of successfully received the indicators, the optimal set of routing paths including a combination of paths over multiple channels.
26. (Previously Presented) The access node of claim 25, wherein the plurality of channels comprises transmission channels according to at least one of 802.11(a), 802.11(b), 802.11(g), 802.11(n) transmission protocols.

27. (Cancel) The access node of claim 25, wherein the access node determining an optimal set of routing paths comprises determining a path quality of the available paths, and selecting the optimal paths based upon a selection criteria.
28. (Previously presented) The access node of claim 25, wherein the indicators comprise beacons originating at the upstream gateways.
29. (Previously presented) The access node of claim 28, wherein the beacons are retransmitted by the upstream access nodes after the beacons have been modified to include selected upstream routing information.
30. (Previously presented) The access node of claim 25, wherein selected upstream paths between each upstream access node and upstream gateways can include a combination of paths, over multiple channels.
31. (Previously presented) The access node of claim 25, further comprising the access node transmitting a modified indicator over a plurality of channels, the modified indicator including the optimal set of routing paths between the access node and the at least one upstream gateway.
32. (Currently amended) A mesh network comprising:  
at least one gateway, each gateway transmitting beacons through each  
of a plurality of transmission channels at a predetermined rate;  
a plurality of access nodes, each access node receiving beacons  
through at least one of the transmission channels, each access node selecting  
routing paths based upon ~~path indicator information within the~~ a persistence  
of successfully received beacons, the routing paths selected from the plurality

of transmission channels, the selected set of routing paths including a combination of paths over multiple channels; and

a client, the client receiving beacons through at least one of the transmission channels from at least one of the access nodes.

33. (Previously presented) The mesh network of claim 32, wherein the plurality of channels comprises transmission channels according to at least one of 802.11(a), 802.11(b), 802.11(g), 802.11(n) transmission protocols.
34. (Previously presented) The mesh network of claim 32, wherein the access node determining an optimal set of routing paths comprises determining a path quality of the available paths, and selecting the optimal paths based upon a selection criteria.
35. (Previously presented) The mesh network of claim 32, wherein the indicators comprise beacons originating at the gateways.
36. (Previously presented) The mesh network of claim 35, wherein the beacons are retransmitted by the upstream access nodes after the beacons have been modified to include selected upstream routing information.
37. (Previously presented) The mesh network of claim 32, wherein selected upstream paths between each upstream access node and upstream gateways can include a combination of paths, over multiple channels.
38. (Previously presented) The mesh network of claim 32, further comprising the access node transmitting a modified indicator over a plurality of channels, the modified indicator including the optimal set of routing paths between the access node and the at least one upstream gateway.

39. (New) The method of claim 1, wherein the access node re-broadcasting beacons corresponding to the selected routing path, over each of the plurality of channels comprises:

the access node adjusting a link quality and path quality associated with the received beacons based on whether beacons are received within a routing cycle;

the access node retransmitting modified beacons over each of the plurality of channels if the path quality is above a threshold.